

## **MATERIAL SPECIFICATIONS FOR MULTI-CHANNEL VIDEO ENCODER**

Ensure that multi-channel Video Encoder conforms to the following specifications:

### A. Standards and Certifications

1. UL Listed
2. Institute of Electrical and Electronics Engineers (IEEE) and Operating Standards:
  - a. IEEE 802.3 10Base-T
  - b. IEEE 802.3u 100Base-TX
  - c. IEC60068-2-1:1990 + A1:1993 + A2: 1994
  - d. IEC60068-2-1:1974 + A1:1993 + A2: 1995
  - e. ISO/IEC 13818
  - f. ISO/IEC 14496-2
  - g. IEC/EN 60950-1
  - h. IEC/EN 60825
  - i. IEC/EN 61000
3. Safety Certifications:
  - a. Electromagnetic Emissions: Federal Communication Commission (FCC) Part 15, (Sub Part B, Class A)

### B. Functional Requirements

1. Convert analog video and serial PTZ data to MPEG4 Video stream for transmission over Ethernet Network.
2. Compatible with current NJDOT Genetec server software system.
3. Transparent serial port supporting any asynchronous serial protocol.
4. Compression: MPEG-4 simple profile, H.264, MJPEG
5. Number of video streams: Dual Streams
6. MPEG video resolution: Scalable from 176x128 to 704x480 pixels QCIF, 1CIF, 2CIF, 4CIF, 1-30 FPS user selectable for each stream.
7. Bandwidth: 30 Kbps to 6Mbps user selectable for each stream.
8. Transport Protocols: RTP/IP, UDP/IP, SAP, TCP/IP, Multicast IP, Unicast IP, RTSP
9. Other Protocols: DNS, NTP, HTTP, FTP and DHCP client

### C. Management

1. HTML Web Browser with Password Protection, Telnet
2. Flash memory of video codec and firmware upgrade over the network
3. HTTPS based Authentication (For Broadband and ISP applications)

### D. Interface and Connectors

1. Serial Interface (PTZ): EIA RS-422/RS-485  
Transparent serial port supporting any asynchronous serial protocol.
2. Video: 1 Composite, 1Vpp into 75 ohms (NTSC), BNC female connector.
3. Ethernet Network: 10/100Base-T Cat6, RJ45 connector

### E. Indicators

1. LED Indicator showing Power Status
2. LED Indicators showing status and activity of each port

### F. Mechanical Specifications

1. Max. Dimension not to exceed: 17" L X 6.0"W x 1.75" H
2. Max. Weight not to exceed: 6 lb

### G. Environmental Specifications

1. Operating Temperature: 32°F to +122°F
2. Operating Humidity: 10% to 95% non-condensing at 122°F

### H. Electrical Power

1. The power supply is to be equipped with a minimum of a six (6) foot power cord terminating in a standard three (3) prong line plug. Maximum power requirement is not to exceed 10 watts for each unit.

I. Software

1. Provide Software License(s) with the unit.

J. Identification

1. Identify Video Encoder with a metal plate containing the serial number with bar code identification. Provide phenolic nameplate with switch designation shown on Contract Documents. Provide manuals and training documentation, and electronic version of custom configurations on compact disc media.

K. Standard Configuration

Encoder Type	Minimum Number of Required Ports		
	NTSC Video	RS232/422/485	10/100 Base T/Tx
Type A	8	1	1
Type B	12	1	1
Type C	24	1	1

Ensure that the video channel and data channel have the capability to configure to independent IP address and port number.

L. List of Equipment

1. Provide the following with each multi-channel Video Encoder:
  - a. Documentation
  - b. External power supply (if required)
  - c. All required custom connections
  - d. Mounting brackets/shelf (if required)